

TECHNICAL SPECIFICATION SHEET

ZDL7260STSS / ZDL7260STRSS



PRODUCT SPECIFICATIONS

- Available with 60mm backset
- Case size (60mm backset) - 90 x 165mm
- Face plate - 235 x 22 x 3mm
- Stainless Steel latch bolt & dead bolt
- Single throw dead bolt
- Includes grip tight follower spring
- Includes anti-rattle strike and dust box
- Available in square & radius profiles
- All factory QC tested
- Tested to BS EN 12209 : 2003
- FD 30/60 timber door tested
- Certifire tested - CF850
- 10 year mechanical guarantee

STANDARDS



SUITABILITY



ADDITIONAL INFO.



30 minutes & 60 minutes

Category of use	Durability	Door Mass	Fire Resistance	Safety	Corrosion Resistance	Security	Field of Door	Type of Key	Type of Spindle	Key Identification
3	X	8	1	0	G	2	B	C	2	0

CODE	DESCRIPTION	FINISH	ADDITIONAL INFO.
ZDL7260STSS	ZDL Din Lock Series	SS	Single Throw Sashlock
ZDL7260STRSS	ZDL Din Lock Series	SS	Single Throw Sashlock - Radius
			<p>URS is a member of Registrar of Standards (Holdings) Ltd.</p>