SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : HUILE PLAN DE TRAVAIL EMULSION Product code : RS00506.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Oil

1.3. Details of the supplier of the safety data sheet

Registered company name : Groupe V33 / V33. Address : Rue Croix Bernard La Muyre.39210.DOMBLANS.FRANCE. Telephone : 03.84.35.00.33. Fax : 03.84.44.63.18. fds.produits@v33.com www.v33.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA http://www.centres-antipoison.net.

Other emergency numbers

UK - National Poisons Information Service

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :	
EUH208	Contains 2-BUTANONE OXIME. May produce an allergic reaction.
EUH208	Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.
EUH208	Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.
Precautionary statements - G	eneral :
P102	Keep out of reach of children.
Precautionary statements - Pr	revention :
P271	Use only outdoors or in a well-ventilated area.
Precautionary statements - Di	isposal :
P501	Dispose of contents/container to a waste collection center (contact the local authority)

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 616_014_00_0	GHS06, GHS05, GHS08	[1]	0 <= x % < 0.85
CAS: 96-29-7	Dgr	[2]	
EC: 202-496-6	Acute Tox. 3, H311		
REACH: 01-2119539477-28	Skin Sens. 1, H317		
	Eye Dam. 1, H318		
2-BUTANONE OXIME	Carc. 2, H351		
INDEX: 613-088-00-6	GHS05, GHS07, GHS09		0 <= x % < 2.5
CAS: 2634-33-5	Dgr		

SAFETY DATA SHEET (REGULATION	I (EC) n° 1907/2006 - REACH)
HUILE PLAN DE TRAVAIL EMULSION	I - RS00506

JILE PLAN DE TRAVAIL EMULSION - RS00506		
EC: 220-120-9	Acute Tox. 4, H302	
	Skin Irrit. 2, H315	
1,2-BENZISOTHIAZOL-3(2H)-ONE	Eye Dam. 1, H318	
	Skin Sens. 1, H317	
	Aquatic Acute 1, H400	
	M Acute = 1	
INDEX: 613_088_00_6	GHS06, GHS05, GHS09	0 <= x % < 2.5
CAS: 2634-33-5	Dgr	
EC: 220-120-9	Acute Tox. 4, H302	
	Skin Irrit. 2, H315	
1,2-BENZISOTHIAZOL-3(2H)-ONE	Skin Sens. 1, H317	
	Eye Dam. 1, H318	
	Acute Tox. 2, H330	
	Aquatic Acute 1, H400	
	M Acute = 1	

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor. Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

- In the event of a fire, use :
- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Unsuitable methods of extinction

- In the event of a fire, do not use :
- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

- Do not breathe in smoke.
- In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Do not allow to freeze

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

Occupational exposure limits :

- Germany - AGW (BAuA - TRGS 900, 07/06/2017) :

CAS	VME :	VME :	Excess	Notes	
96-29-7		0,3 ppm		8 (I)	
		1 mg/m3			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

2-BUTANONE OXIME (CAS: 96-29-7)

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) HUILE PLAN DE TRAVAIL EMULSION - RS00506

Final use: Exposure method: Potential health effects: DNEL :

Final use: Exposure method: Potential health effects: DNEL :

Predicted no effect concentration (PNEC):

2-BUTANONE OXIME (CAS: 96-29-7) Environmental compartment: PNEC :

Environmental compartment: PNEC :

Workers.

Dermal contact. Long term local effects. 1.3 mg/kg de poids corporel/jour

Dermal contact. Long term systemic effects. 1.3 mg/kg de poids corporel/jour

Inhalation. Long term local effects. 0.94 ppm

Inhalation. Long term systemic effects. 94 ppm

Consumers. Dermal contact. Long term local effects. 0.78 mg/kg de poids corporel/jour

Dermal contact. Long term systemic effects. 0.78 mg/kg de poids corporel/jour

Inhalation. Long term local effects. 2 mg de substance/m3

Inhalation. Long term systemic effects. 2 mg de substance/m3

Fresh water. 0.256 mg/l

Waste water treatment plant. 17.7 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVC (polyvinyl chloride)

- PVA (Polyvinyl alcohol)

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state :	Viscous liquid.	
Important health, safety and environmental information		
pH :	Not stated.	
	Slightly basic.	
Boiling point/boiling range :	Not relevant.	
Flash point interval :	Not relevant.	
Vapour pressure (50°C) :	Below 110 kPa (1.10 bar).	
Density :	1-1.05	
Water solubility :	Dilutable.	
Melting point/melting range :	Not relevant.	
Self-ignition temperature :	Not relevant.	
Decomposition point/decomposition range :	Not relevant.	

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Acute toxicity :

2-BUTANONE OXIME (CAS: 96-29-7)	
Oral route :	LD50 = 2326 mg/kg
	Species : Rat
Dermal route :	LD50 = 1000 mg/kg
	Species : Rabbit
Inhalation route (Vapours) :	LC50 = 13200 mg/m3
	Species : Rat

11.1.2. Mixture

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

1. Toxicity	
2.1.1. Substances	
2-BUTANONE OXIME (CAS: 96-29-7)	
Fish toxicity :	LC50 > 100 mg/l Duration of exposure : 96 h
	NOEC = 50 mg/l
Crustacean toxicity :	EC50 = 201 mg/l
	Duration of exposure : 48 h
	NOEC = 100 mg/l
Algae toxicity :	ECr50 = 11.8 mg/l
	Duration of exposure : 72 h
	NOEC = 2.56 mg/l
1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)	
Fish toxicity :	Duration of exposure : 96 h
Crustacean toxicity :	Duration of exposure : 48 h
	NOEC = 1.21 mg/l
	Species : Daphnia magna
	Duration of exposure : 21 jours
Algae toxicity :	Duration of exposure : 72 h
2.1.2. Mixtures	
No aquatic toxicity data available for the mixture.	
2.2. Persistence and degradability	
2.2.1. Substances	
1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)	
Biodegradability :	Rapidly degradable.
2-BUTANONE OXIME (CAS: 96-29-7)	
Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.
2.3. Bioaccumulative potential	
2.3.1. Substances	
1,2-BENZISOTHIAZOL-3(2H)-ONE (CAS: 2634-33-5)	
Octanol/water partition coefficient :	log Koe = 0.7 OCDE Ligne directrice 117 (Coefficient de partage (p-octanol/eau), méthode
	OCDE Ligne directrice 117 (Coefficient de partage (n-octanol/eau), méthode HPLC)
Bioaccumulation :	BCF = 6.95
	OCDE Ligne directrice 305 (Bioconcentration: Essai dynamique chez le
	poisson)
	poisson
2-BUTANONE OXIME (CAS: 96-29-7)	poissony

Bioaccumulation:

BCF < 100.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC. CAUTION: Oil cloths can self combust. Do not leave impregnated cloths in bundles. Before discarding lay them flat outside to dry to avoid a fire hazard

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2015).

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.
- Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) HUILE PLAN DE TRAVAIL EMULSION - RS00506

HUILE PLAN DE TRAVAIL EMULSION - RS00506		
H318	Causes serious eye damage.	
H330	Fatal if inhaled.	
H351	Suspected of causing cancer.	
H400	Very toxic to aquatic life.	

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.